




<b>CABLE TYPE</b>	Non-Metallic Armored Distribution Cable
<b>CABLE CODE</b>	I/A-V(ZN)H(BN)2Y
<b>STANDARDS</b>	IEC 61034; IEC 60332-2; IEC 60754-2; IEC 60794-1&2, IEC 60793-1&2

CROSS SECTION	CABLE DRAWING
 <ol style="list-style-type: none"> <li>1. Outer Sheath ( PE Jacket)</li> <li>2. Non-Metallic Glass Yarn Armor</li> <li>3.HFFR Inner Jacket</li> <li>4. 900. Mic. Tight Buffer</li> <li>5.Aramide Yarns</li> <li>6. OpticFiber</li> </ol>	

KEY FEATURES	APPLICATIONS
 <p>Easy to Strip (Tight Buffer) Waterproof Glass Yarn Armored Complete Dry Design High Crush &amp; Impact Resistance Halogen Free Fire Retardant / Low Smoke Zero Halogen (I-V(ZN)H(BN)H version) Moisture Barrier Rodent Resistant Flexible Enforcement with Non-Metallic Strength Members Direct Termination of Fibres in the Field</p>	<p>Inter Building and Intrabuilding Voice or Data Communication Networks WAN Installed in Ducts &amp; Conduits In and Outside Plant Campus Cabling Fttx Cabling Riser and General Horizontal Applications LAN Environments requiring dielectric extra protection Direct Connection to Terminal Equipments Interconnection of Distribution Boxes, Distribution Frames and Customer Equipment and Between the Floors and Buildings</p>

### SPESIFICATIONS

	SPECIFICATIONS					
	4	6	8	12	16	24
Fibres	4	6	8	12	16	24
Strength members	Aramid Yarns					
Tight Buffer Ø (µ)	900±50					
Inner jacket	LSZH					
Armour	Water Blocking Glass Yarn					
Outer jacket	Polyethylene-Flame reterdant					
Weight (Kg/Km)	64	70	74	82	98	110
Outer Ø (mm)	7,5	8	8,3	9	9,8	10,3
Tensile Load Perm/Inst (N)	600/1000	600/1000	800/1200	800/1200	1000/1800	1200/2000
Optical Characretistic	62,5/125 OM1		50/125 OM2	50/125 OM3	50/125 OM4	9/125 G.652-D
Bandwith (nm)	850/1300		850/1300	850/1300	850/1300	1310/1550
Attenuation (max dB/km)	3.2/1.2		3.0/1.0	2.8/0.8	2.7/0.7	0.34/0.25
Crush (N)	1500 (IEC 60794-1-2 E3)					
Temperature Range	-20 °C to +60 °C (IEC 60794-1-2 F1)					
Min. Bending Radius	20 x Outer Ø (IEC 60794-1-2 E11)					

This document is a property of INFOKS KABLO Tic. Ltd. Sti. and must not be copied or damaged in any form, wholly or in part w/o written permission from INFOKS KABLO Tic. Ltd. Sti. The specifications indicated in this document are not contractual and can be modified w/ notification