




CABLE TYPE	Pigtail
CABLE CODE	j-H
STANDARDS	DIN VDE 0888 Part 2; IEC 61034; IEC 60332-1; IEC 60754-2

CROSS SECTION	CABLE DRAWING
 <p> <b>01</b> 1. 900 mic. HFFR Sheath  <b>02</b> 2. 250 mic. Optical Fiber Coating and Color  <b>03</b> 3. 9/50/62,5 mic. Optical Fiber Core         </p>	

KEY FEATURES	APPLICATIONS
<p>  </p> <p>           Easy to Strip            Easy and Direct Termination            Low Installation Cost            Dry Design            All Dielectric            Halogen Free Fire Retardant / Low Smoke Zero Halogen         </p>	<p>           Pigtail and Jumper Connections            Indoor Interconnect and Patchcord Applications         </p>

SPESIFICATIONS

	SPESIFICATIONS
Fibers	1
Outer Jacket	LSZH
Colour	Orange (MM62) / Blue (MM50) / Yellow (SM)
Weight (kg/km)	0,9
Outer Ø (mm)	900 ±50
Tensile Load Perm/Inst(N)	10
Max. Length (m)	8000
Temperature Range	-10 °C to +60 °C (IEC 60794-1-2 F1)
Min. Bending Radius	20 x Outer Ø (IEC 60794-1-2 E11)

This document is a property of INFOKS KABLO Tic. Ltd. Sti. and must not be copied or damaged in any form, wholly or in part w/o written permission from INFOKS KABLO Tic. Ltd. Sti. The specifications indicated in this document are not contractual and can be modified w/o notification